



2021 MODIFIED DIVISION

RULES QUESTIONS? Please e-mail the track by sending your e-mail to racekinross@gmail.com and carbideyip.500@yahoo.com

Please also read and understand the General Rules, (published separately) they apply to all classes / competitors.
Kinross Speedpark/Fox Boyz Racing officials decision is **FINAL!**

NOTE: RACECEIVERS AND TRANSPONDERS ARE MANDATORY!

All drivers will be required to operate a Raceceiver during all hot lap sessions, qualifying and race events. The devices will be used for on-track safety notice, disciplinary action and line-up procedures.

Raceceiver is to be tuned to 454.0000.

Any driver who does not have a Raceceiver on, or operational, will be instructed to leave the track. NO EXCEPTIONS!

Westhold transponders are used for scoring purposes at Kinross Speedpark. Driver's can purchase these units independently or can contact the track for pricing. Compatible units are orange or yellow (green does not work)

Radios and mirrors ARE NOT permitted for regular events.

BRAKES

MUST be cast steel OEM type ONLY, operative on all 4 wheels, drum or disc. Must maintain minimum OEM dimensions for hub/rotor and calipers, cannot be drilled or lightened. Bolt pattern may be changed. Larger studs allowed. Front brake rotors MUST be stock type. Rear rotors may be aftermarket, minimum .810 inch thick, vented rotors only. No scalloped or drilled rotors.

BODY

1. Roof height to be 46" Max. – 42" Min.

2. Outside of tires must be the widest part of car. Maximum overall width, front and rear, shall not exceed 78 inches from outside of tire, to outside of tire

DRIVE SHAFT

Minimum 2.5 inch diameter, steel drive shaft, painted white. Steel slip-yokes only. 360 degree drive shaft loop required and must be constructed of at least .25 inch by 2 inch steel or equivalent, mounted 6 inches back from front u-joint.

ENGINE

Any American make engine allowed. Steel block. No machine work to the outside of block (lightening). Wet sump oiling system only.

****SINGLE STAGE EXTERNAL PUMP ALLOWED AS LONG AS OIL REMAINS IN PAN(NO EXTERNAL TANKS).**

One (1) naturally aspirated two or four barrel carburetor only. (No fuel injection) No magnetos. Oil pump must be in front of engine.

FRAMES

1964 or newer OEM perimeter American made rear wheel drive passenger car frame only. Reproduction 68-72 Chevelle frames are approved - AFCA 1968-1972 Chevelle Replacement Frame (Part #40000) and components (Part #'s 40013, 40014, 40015, 40016, 40017 and 40018) are permitted.

Howe OEM replacement fabricated Impala Type Front Frame (Part #35809) and Chevelle Type Front Frame (Part #35810) will be allowed but must add 60 lbs total, 30 lbs. to each frame rail at built in ballast mounts (Tech officials discretion). Howe frames must have CNC cut part number tag along with trademarked Howe 'H' logo on each frame rail. Must be original and from factory, no altering.

No sports car frames. 2002 & up Ford Crown Vic or similar frames are allowed. Strut front suspension of any kind allowed must add 50 lbs. No tube clips allowed. Frame must be full and complete, cannot be widened or narrowed, and must be able to support roll cage on both sides. . Minimum wheelbase 108 inches, maximum 112 inches, both sides. Maximum overall width, front and rear, shall not exceed 78 inches from outside of tire, to outside of tire. Exceptions: Weight jack in original center line of spring tower; frame may be cut a maximum 36 inches forward from center of rear housing; horns may be removed in front of steering box; front cross member may be notched and boxed for radiator and/or steering clearance; maximum 7 inch wide opening in side of spring tower for spring removal. OEM upper A mounts may be replaced with aftermarket mounts. Maximum 4 inch wide by 4 inch tall frame stiffener may be welded directly to outside of left OEM frame rail. Left side OEM frame rail may be notched for seat and foot clearance. Right side frame must have top and bottom of frame no holes in rails.

ROLL CAGE

Maximum 4 inch wide by 4 inch tall frame stiffener may be welded directly to outside of left OEM frame rail. Left side OEM frame rail may be notched for seat and foot clearance Must consist of continuous hoops, minimum 1.75 inch O.D. tubing, with a minimum wall thickness of .095 inch for the main cage. Frame mounted in at least 6 places, low carbon or mild steel recommended. Must consist of a configuration of front, rear, and top hoops connected by tubing on the sides or side hoops. Driver's head must not protrude outside cage with helmet on. Roll cage must be securely supported and braced with minimum 1 cross bar in top halo. Foot protection bar(s) required. Main cage no further forward than rear of engine. All bars forward of the cage must be lower than the hood. "X" OR "Z" BAR BEHIND DRIVERS HEAD .

DOOR BARS; All driver side door bars and uprights must be a minimum 1.75 inch and .095 inch wall thickness. Minimum 4 driver side door bars, parallel to the ground and perpendicular to the driver, and welded to the front and rear roll cage. Passenger side must have at least 1 cross door bar, horizontal or angled, and 1 top door bar, minimum 1.5 inch O.D. Steel door plate, 16 gauge (.065) minimum thickness, must be securely welded to outside of the driver side door bars and cover the area from top door bar to bottom door bar and from rear hoop down post to front cage down post.

REAR END

All steel. Closed, steel tube Quick changes allowed. Safety hubs (floater) mandatory. Steel axles only. No cambered rear ends. One (1) piece drive flange only. All components must be steel. Exceptions: lowering blocks, axle caps, rotor plates, and drive flanges. NO COVER ON REAR END OF BODY. . ALL CAR RUNNING A BIRD CAGE TYPE REAR END MUST HAVE A 1/16 STEEL PLATE or 1/8 alum plate behind the seat From the top bar to bottom to and from the left side to right 3 inches pass seat . THIS WILL BE IN place or you don't race.

REAR SUSPENSION

No independent rear suspension. All components must be steel. No covers allowed. All trailing arms/link bars must be made of steel tubing (aluminum hex tube will be acceptable) Rear of frame may be altered to accept leaf or coil springs. Steel coil-over eliminators, and steel or aluminum (5") coil-over kits, allowed on the rear only. Must conform to shock and spring rules. No rear sway bars.

SPOILER

A 4 inch by 66 inch spoiler 45 deg to the deck is allowed, with all braces to the rear of the spoiler. Spoiler must be 1 piece.

SHOCKS

NO EXTERNAL CANISTERS (SHRADER VALVES PERMITTED) 1 SHOCK PER WHEEL, 1 ADDITIONAL SHOCK ALLOWED IN THE LIFT/PULL BAR AREA. ALL SHOCKS MUST BE EASILY REMOVED (NO COVERS ALLOWED) You can run single adjustable shocks no double adjustable , no blow off shafts.

SPRINGS

Steel coil and leaf springs allowed. Coil springs must be at least 4.5 inches O.D. No torsion bars or air bags. Exception: Pull bar may utilize smaller O.D. springs.it

TIRES

1. Hoosier D800 tire ONLY.

2. Tires you qualify on must be ran in the feature event. Tires will marked prior to qualifying and monitored by track officials.

In the event of a flat or replacement tire needed, must be approved by official.

3. ABSOLUTELY NO TIRE SOAKING OR ALTERING OF THE THE TIRE OF ANY KIND ALLOWED AT KINROSS SPEEDPARK.

This does not mean you can go down to a certain softness or Durometer number ... it states NO SOAKING OR TIRE ALTERING PERIOD.

At any time track officials may take a tire sample from any tire(s) to be submitted to laboratory for testing.

If the tire sample sent in is found to have been altered, the driver will forfeit their earned money and points from that night of racing and receive a 2 race day suspension.

If the tire sample is found to be clean, all points and money will be administered.

Refusal to comply with tire confiscation for testing, the driver will forfeit his/her pay and points for the night and be administered a two race day suspension.

When a tire samples are taken for laboratory testing, the drivers pay will be withheld until results are returned to the track determining if there was soaking, altering etc.

TRANSMISSION

Must have at least two forward gears and one reverse, plus a neutral position. With engine running and car in still position, must be able to engage car in gear and move forward, then backward. OEM production type or approved aftermarket transmissions (Bert, Brinn, Falcon) allowed. (2-speed, 3-speed, 4-speed and automatic). No 5-speed or more transmissions, No 'in and 'out boxes allowed. Standard clutch type transmissions must have a blow proof bell housing (steel or aluminum). Automatic transmissions must have an approved scatter shield..

WEIGHT

1. 2400 lbs total weight, 1000 lbs right side, with driver in car, in race trim before the feature.

WHEELS

Eight (8) inch steel wheel only, measured from inside bead to inside bead. No screws or rim mounted bleeder valves. Steel and aluminum wheel spacers are allowed.

WINDSHIELDS

1. There will be no full front windshields, and side and rear must remain open

OTHER

1. Feature winners will be placed at the back of the field upon their next appearance at the Speedpark. These drivers position will be behind ALL cars, including Fast Qualifier, at the discretion of track officials.